
BenchRocker™2D onnonnamental management of the second secon BenchRocker™3D



These rockers are designed to provide the precise speeds and tilt angles required for a broad range of molecular and biological mixing applications. The user can adjust both parameters to match the vessel size and the

The rocking speed and tilt angle are both easily adjustable in seconds. At low speeds and minimal tilt angles, both models (2D for "see-saw"

volume of liquid being mixed, vielding optimum results.

motion or 3D for "gyratory" motion) provide a gentle wave effect for non-foaming mixing, as is required for most blot washing and gel work. When set to higher speeds and more extreme tilt angles, they

produce aggressive agitation for vigorous sample mixing.

The BenchRocker 2D and 3D can accept stackable platforms

(clearance = 2.75 in.). All platform mats are autoclavable. Both models have maintenance free brushless motors and are safe for use in cold rooms and incubators.

Two or three dimensional motion

Adjustable speed and tilt angle

- Dual platform option expands workspace

Safe for incubator/cold room use

Technical Data

Tilt Angle: Platform Size (2D): Platform Size (3D): Load Capacity: Operating Temp. Range: Dimensions (WADAH):

Variable, 0 to 30° 35x30 cm / 14x12 in. 2.0 kg / 4.4 lbs. +4°C to +65°C 35 x 30 x 20 cm 14 x 12 x 8 in.

230V AC, 50 Hz, 0.15A

Variable, 2 to 30 rpm

manana

Ordering Information

BR2000-STACK

B3D2300*

BR1000-STACK

BR2000* BenchRocker 2D variable speed rocker with

flat mat platform

Optional stacking platform (14x12 in.) with flat mat

BenchRocker 3D variable speed rocker with dimpled and flat mats

Optional stacking platform (12x12 in.) with flat mat BR1000-STACK-D Optional stacking platform (12x12 in.) with dimpled mat

LaBungee™ elastic tie downs with hooks, pk.4



SoCal Biomedical Orange County, CA Phone: (424) 400-2340 Fax: (323) 372-3546 www.socalbiomedical.com