

# Model F7

-90°C  
-130°F

## ARCTIK MINI SERIES

- Low energy consumption
- Low noise level
- Low heat dissipation
- Insulated inner doors
- Castors and door key lock
- Ergonomic loading
- Heated door frame
- 100% HCFC/CFC free
- Porthole for external temperature probes

## ALL STANDARD FEATURES

- Micro processor controller with digital display
- Approx. 72 hours battery back up for alarms, loggings and temperature display in case of power cut
- Prepared for GSM alarm
- Prepared for connection of 2 additional probes
- Auto cycle in case of probe failure
- Ambient temperature display
- Direct download of logged data on USB memory stick
- Direct upload of new software via USB memory stick
- 3-level password protected
- Battery level indication
- Display text available in different languages
- Temperature graph
- Integrated data logger
- RS485/RS232 interface
- Integrated memory for 30 years
- Visual and acoustic alarm
- Adjustable high/low temperature alarm
- Power failure alarm
- Probe failure alarm
- Instrument failure alarm
- Open door alarm
- Contact for remote alarm
- Shows all alarms

Arctik Mini -86°C range are products of our passion, striving after excellence when we offer the best in ultra low temperature freezing. All features such as alarms and data logging functions are always included as standard. The ULUF -86°C series is produced with the true and original single compressor technology.



GSM alarm module for optimal safety (optional)

Battery backup - 72 hours



Integrated data logger with memory



RS485/RS232 interface



On/off protection



MODEL	ULF7
Item code	US-DAI 1390
Dimension exterior WxDxH (Inches)	15.7 x 24.8 x 26.2
Capacity (cu.FT)	0.25
Temperature range (°F)	-130 / -40
Temperature range (°C)	-90 / -40
Power supply (V)	110
Frequency (Hz)	60

# W. VERLY

# Technical specifications

Item code	ULF7
Dimension exterior WxDxH (Inches)	15.7 x 24.8 x 26.2
Capacity (cu.FT)	0.25
Dimension interior WxDxH (Inches)	5.9 x 5.6 x 12.2
Insulation (Inches)	4.7
Temperature range (°F)	-130 / -40
Temperature range (°C)	-90 / -40
Max. ambient temperature (°F)	77
Power supply (V)	110
Frequency (Hz)	60
Power consumption (KWH/24H)	4.6
AMP (A)	2.5
Weight (lb)	83
Shipping weight (lb)	119
Shipping dimensions WxDxH (Inches)	31.5 x 20.1 x 34.3
No. of compressors	1
Visual / acoustic alarm	Yes
Power failure alarm	Yes
Adjustable high/low temperature alarm	Yes
Open door alarm	Yes
Probe failure alarm	Yes
Alarm display as text - not codes	Yes
Contact for remote alarm	Yes
Prepared for GSM alarm module	Yes
Approx. hrs of battery back up for alarms and temperature display in the event of power cut	72 hours
Porthole for installation of PT100/CO <sub>2</sub> back up	Yes
Digital display	Yes
Data logger	Yes
RS 232 interface	Yes
RS 485 interface	Yes
USB up/down load	Yes
Defrost manual/auto	Manual
Castors	No
Chart recorder	Optional
Shelves (pcs) / drawers (pcs)	No
Basket (pcs)	No
Sub doors (pcs)	1
Lighting	Yes
Lock	Yes
Inner liner material	Stainless steel
Cabinet material	Varnished steel / Stainless steel
Colour (exterior)	White / Stainless steel
Refrigerant	Ep88


# Optional



**1** The GSM alarm module sends a SMS message to one or several coded telephone numbers in case the temperature exceeds a fixed range.



**2** SVS voltage stabilizers for excellent output voltage stability in case the voltage rises or drops.



**3** Chart recorder for documentation of the temperature condition over a certain period of time.



**4** CO<sub>2</sub> back up system ensures optimized safety.



**5** Cryo gloves protect your hands and prevent frost bites when handling samples which are stored at down to -160 °C.



CO<sub>2</sub>CARE



socalbiomed.com

\* Optional, please contact us  
We reserve the right to change specifications without notice and subject to errors.